

JAPAN GAFFER TAPE

STAGE | CINEMA | EVENTS | AUTOMOTIVE | AICRAFTS

ultraMATT | MATT | trueGAFF | EXPO



eco friendly



Your Choice — Your Quality

@MATT - 80Mesh Cloth Tape | Premium Grade - UV + Temp Resistant

Backing: Cotton Cloth with Premium Matte Finish LDPE coated

Adhesive: Rubber based - Smooth, controlled unwind + UV +Temp resistant

Tensile strength: 20 lbs. per inch

Elongation: 2%

Total Thickness: 12 mils (290-310 micron)

Adhesion to steel: 50 oz./in (5,4 N/cm) - based on USA standarts

Service Temperature: 50°F to 180°F (10°C to 90°C)

9 Colors Available: Black, White, Grey, Red, Yellow, Electric Blue, Green, Chroma Blue,

Chroma Green.

Adhesive Power:

No Residue:

Tear by hand 90 degree:

Writing on surface:

O O O O O O O
O O O O
O O O O
O O O O
O O O O
O O O O
O O O O
O O O O
O O O O
O O O O
O O O O
O O O O
O O O O
O O O O
O O O O
O O O
O O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O O
O O
O O O
O O
O O O
O O
O O O
O O
O O
O O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O
O O

Possible size: 1 in (25mm) / 2in (50mm) / 3 in (72mm) - Length: 60ya (50m)

Reflection: 2,5 %



@MATT STRONG - 145Mesh ProPower Grade | UV + Temp + Abrasion Resistant

Backing: Heavy Duty Cotton Cloth with Matte Abrasion resistant coated

Adhesive: Rubber based
Tensile strength: 20 lbs. per inch

Elongation: 2%

Total Thickness: 12 mils (310-320 micron)

Adhesion to steel: 75 oz./in (8,3 N/cm) - based on USA standarts

Service Temperature: 50°F to 180°F (10°C to 90°C)

3 Colors Available: Black, White, Red.

Adhesive Power:

No Residue:

Tear by hand 90 degree: horizontal perfect / vertical good
Writing on surface: good with permanent marker + pen

Possible size: 2in (50mm) / 3 in (72mm) - Length: 27-30ya (25m)

Reflection: 1,9 %



@trueGAFF - 120Mesh Heavy Duty Cloth Tape | Professional Grade

Backing: Matte finish Cotton Cloth
Adhesive: Natural Rubber based
Tensile strength: 50 lbs. per inch

Elongation: 4%

Total Thickness: 12 mils (310 micron)

Adhesion to steel: 57 oz./in (5,8 N/cm) - based on USA standarts

Service Temperature: 50°F to 180°F (10°C to 90°C)

11 Colors Available: Black, White, Grey, Red, Brown, Violet.

FL. Orange, FL. Yellow, FL. Pink, FL. Blue, FL. Green.

Adhesive Power:

No Residue:

Tear by hand 90 degree: horizontal superior / vertical superior

Writing on surface: best writing

Possible size: 1/2 in -12mm / 1in - 25mm / 2in - 50mm / 3 in - 72mm / 4 in - 100mm

Length: 6ya - 5m / 11ya - 9m / 18ya - 15m / 25ya - 23m / 50ya - 46m

Reflection: 0,5 %





@ultraMATT - 76Mesh Cloth Tape | Ultra Low Reflection < 0,5%



Backing:

Adhesive:

Tensile strength:

Elongation:

Total Thickness:

iutai iiiiukiiess.

Adhesion to steel:

Service Temperature: 8 Colors Available:

Adhesive Power: No Residue:

Tear by hand 90 degree:

Writing on surface:

Possible size:

Reflection:

Cotton Cloth with ultraMatte Finish LDPE coated

Natiral Rubber based

20 lbs. per inch

2%

11 mils (290-300 micron)

50 oz./in (5,4 N/cm) - based on USA standarts

50°F to 149°F (10°C to 65°C)

Black, White, Grey, Deep Yellow.

FL. Orange, FL. Green, FL. Yellow, FL. Pink.



horizontal perfect / vertical perfect good with permanent marker + pen

1 in (25mm) / 2in (50mm) / 3 in (72mm) - Length: 60ya (50m)

05%



@EXPO - 40Mesh | @UTILITY - 50 Mesh | @WARNING @B2B - 70Mesh | @DS



@EXPO - general use

Backing: 40Mesh Cotton + Glossy LDPE Adhesive: Synthetic Rubber based Total Thickness: 7 mils (170 micron) Adhesion to steel: 75 oz./in (8,3 N/cm) Service Temperature: 50°F to 113°F (10°C to 45°C)

3 Colors Available: Grey | Black | Red Adhesive Power:

No Residue:

Reflection: up to 25 %



@WARNING - industrial use

Backing: 70Mesh Cotton + Glossy LDPE
Adhesive: Natural Rubber based
Total Thickness: 11 mils (290 micron)
Adhesion to steel: 57 oz./in (5,8 N/cm)
Service Temperature:
50°F to 113°F (149°C to 65°C)
Colors Available: Yellow-Black
Adhesive Power:

Na Davidea

No Residue:

Reflection: up to 30 %



@UTILITY - general use

Backing: 50Mesh Cotton + Glossy LDPE Adhesive: Natural Rubber based Total Thickness: 9 mils (220 micron) Adhesion to steel: 75 oz./in (8,3 N/cm) Service Temperature: 50°F to 113°F (149°C to 65°C) 3 Colors Available: Black/White/Red/ Adhesive Power:

No Residue:

Reflection: up to 27 %



@DARKSIDE - BLACK2BLACK

Backing: 72Mesh Matte Finish Cotton Adhesive: BLACK Natural Rubber Total Thickness: 11 mils (290 micron) Adhesion to steel: 50 oz./in (5,4 N/cm) Service Temperature: 50°F to 113°F (149°C to 65°C) Colors Available: Black2Black

Adhesive Power:

No Residue:

Reflection: less than 1%

HIGH QUALITY CLOTH TAPE «DGTape» - Developer of Gaffer Tape

DG Tape® - Strong and versatile, gaffer tape is a heavy-duty tape used often in entertainment and media productions, including theatre, film, television and photography work. The DGTAPE adhesive itself is easy to remove. For ease of use, gaffer tape comes in many colors to allow for multiple set-ups and uses in a single production.

DG Tape® tapes are always an excellent result.

Quality Standart: ISO 9001, Japan Industry Standart - JIS 0237

Product Info

Most commonly, it is used for:

- in media industry: Marking off areas on a stage for actors like sight lines or centers; Labeling and/or securing sound boards and cables; Indicating light placements; Repairing props, curtains and other stage omponents on the fly; Ensuring adjustments to microphones and sound packs are kept in place; Affixing camera accessories like external flashes;
- **at home**: for sealing and waterproofing on an ongoing basis, covering and marking sharp edges, fixing and isolating wires, sealing tin boxes and pipes, and much more!
- **industrial use**: black-out tapes, for strapping and reinforcing heavy pipes, profiles, sticking drilled and other holes.

Features:

- High adhesion even to rough surfaces.
- Excellent tensile strength.
- Easy to tear with hands at a right angle, lengthwise or cross direction.
- Easy to write on it (matte surface).
- Elastic and pleasant to use.
- Leaves no traces of glue on the surface after removal.
 In rare cases some traces can remain on rubber and leather surfaces covered with protectional layer or when heated to more than 65 ° C. Test on your surfaces before prolonged use. In any case residues of glue can be removed very easily by the tape itself.



Removing the Tape

For best results, remove the tape at an angle of about 45°. If the angle is more than 90° or in case of residual adhesive layer on the surface, you can remove adhesive residues from the surface with the same tape or new piece of tape.











Tips and Tricks

It is very important to follow certain rules when applying tapes. First, we recommend testing the bonded surface for compatibility. Since in practice there are surfaces of various materials, tests performed by the user are most effective.

Always check the warnings and recommendations of the manufacturers.



















Distributors and Dealers Program:

DGS USA LLC, California | Nevada | Florida | NewYork

+1 (213) 221-10-51 | dgcase.com | dgtape.us | sale@tapeandcase.com

DGS Russia, Moscow

+7 (495) 241-03-17 | dgs.com.ru | sale@dgs.com.ru

Your personal contact manager:

